


## Features

#### \* High reliability

\* Rectification for high voltage power supply of magnetron in Micro wave owen and others





HV 4.5Χ15, Φ1.2						
DIM	INCHES		MM			
	MIN	MAX	MIN	MAX		
А	0.945		24			
В	0.583	0.598	14.8	15.2		
С	0.046	0.048	1.17	1.23		
D	0.169	0.185	4.3	4.7		

#### Maximum Ratings and Thermal Characteristics (TA=25°C unless otherwise noted)


Item	Symbol	2CL3512S	Unit
Repetitive Peak Reverse Voltage	VRRM	12	κv
Average Forward Current	IF(AV)	350	mA
Non-Repetitive Forward Surge Current	IFSM	30	A
Ambient Temperature	Tamb	-40 +100	°C
Maximum Junction Temperature	T(J)	130	°C
Storage Temperature	Tstg	-40 +130	°C

#### Electrical Characteristics (Ta=25°C unless otherwise noted)

Item	Symbol	2CL3512S	Unit
Forward Voltage Drop IF =350mA	VF	12	V
Normal Temperature Reverse Current VR=VRRM	IRM1	5	μΑ
High Temperature Reverse Current TA=100℃ VR=VRRM	IRM2	50	μA




### Ratings and Characteristic Curves



TYPICAL FORWARD CHARACTERISTIC

V<sub>F</sub> Instantaneous Forward Voltage (V)





Repetitive Peak Reverse Voltage (KV)



# Ordering Information

Part No.	Package	Packing Code	Packing
2CL3512S	HV 4.5Χ15, Φ1.2	BXA	50pcs/Bulk

# Disclaimer

Specifications of the products displayed herein are subject to change without notice. JGD or anyone on its behalf, assumes no responsibility or liability for any errors inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in JGD's terms and conditions of sale for such products, JGD assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of JGD products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications.Customers using or seling these products for use in such applications do so at their own risk and agree to fully indemnify JGD for any damages resulting from such improper use or sale.