


ESD3Z...BWS Series

Transient Voltage Suppressors

Features

- * Low clamping voltage
- * Low capacitance
- * For ESD protection











| SOD-323F | | | | | | |
|----------|-------|-------|------|------|--|--|
| DIM | INC | HES | MM | | | |
| | MIN | MAX | MIN | MAX | | |
| Α | 0.091 | 0.110 | 2.30 | 2.80 | | |
| В | 0.045 | 0.053 | 1.15 | 1.35 | | |
| С | 0.063 | 0.071 | 1.60 | 1.80 | | |
| D | 0.010 | 0.016 | 0.25 | 0.40 | | |
| E | 0.031 | 0.043 | 0.80 | 1.10 | | |
| F | 0.004 | 0.006 | 0.10 | 0.15 | | |
| G | 0.016 | 0.024 | 0.41 | 0.61 | | |

Maximum Ratings (T_A=25 °C unless otherwise noted)

| Parameter | Symbol | Value | Unit |
|---------------------------------|-----------------|---------------|------|
| Peak Pulse Power (tp = 8/20 μs) | P _{pk} | 350 | W |
| ESD Voltage | Vesd | 25 | KV |
| Operating Temperature Range | Tj | - 55 to + 150 | °C |
| Storage Temperature Range | Tstg | - 55 to + 150 | °C |

Electrical Characteristics (T_A=25 °C unless otherwise noted)

| Type | Reverse Stand-off Voltage | Reverse Current | Breakdown Voltage | | Clamping Voltage 1) | | Capacitance | | |
|-------------|---------------------------------|--------------------|-------------------|--------------------|---------------------|--------|-------------|------|-------------------|
| Туре | VRWM | Ir at Vrwм | VBR | at I _{BR} | Vc | at Ipp | Cj | at f | at V _R |
| | Max. (V) | Max.(µA) | Min.(V) | mA | Max.(V) | А | Typ.(pF) | MHz | V |
| ESD3Z3V0BWS | 3 | 20 | 3.3 | 1 | 7.5 | 1 | 3 | 1 | 0 |
| ESD3Z5V0BWS | 5 | 5 | 6.1 | 1 | 9.8 | 1 | 3 | 1 | 0 |
| ESD3Z8V0BWS | 8 | 1 | 8.6 | 1 | 13.4 | 1 | 3 | 1 | 0 |
| ESD3Z12BWS | 12 | 1 | 13.5 | 1 | 19 | 1 | 3 | 1 | 0 |
| ESD3Z15BWS | 15 | 1 | 17.39 | 1 | 24 | 1 | 3 | 1 | 0 |
| ESD3Z24BWS | 24 | 1 | 27.27 | 1 | 43 | 1 | 3 | 1 | 0 |

Note: 1) tp = $8/20 \mu s$


Version: 6.1 www.jgdsemi.com




ESD3Z...BWS Series

Transient Voltage Suppressors

Ratings and Characteristic Curves





Ordering Information

| Part No. | Package | Packing Code | Packing |
|-----------------|----------|--------------|--------------|
| ESD3ZBWS Series | SOD-323F | R30 | 3000pcs/Reel |

Disclaimer

Specifications of the products displayed herein are subject to change without notice. JGD or anyone on its behalf, assumes no responsibility or liability for any errors inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied,to any intellectual property rights is granted by this document. Except as provided in JGD's terms and conditions of sale for such products, JGD assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of JGD products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or seling these products for use in such applications do so at their own risk and agree to fully indemnify JGD for any damages resulting from such improper use or sale.

Version: 6.1 www.jgdsemi.com