


Features

- * For surface mounted application
- * Extremely low thermal resistance
- * Easy pick and place
- * High temp soldering: 260°C for 10 seconds at terminals
- * Fast reverse recovery time



RoHS
COMPLIANT



DIM.	SMBF			
	INCHES		MM	
	MIN	MAX	MIN	MAX
A	0.201	0.217	5.10	5.50
B	0.138	0.146	3.5	3.7
C	0.165	0.173	4.2	4.4
D	0.075	0.087	1.90	2.20
E	0.043	0.051	1.10	1.30
F	0.007	0.010	0.18	0.26
G	0.031	0.047	0.80	1.20

Mechanical Data

- * Case: SMBF Molded plastic
- * Terminals: Solderable per MIL-STD-750, Method 2026
- * Polarity: Indicated by cathode band

Maximum Ratings and Electrical Characteristics (T_A=25°C unless otherwise noted)

Type Number	Symbols	FS3ABF	FS3BBF	FS3DBF	FS3GBF	FS3JBF	FS3KBF	FS3MBF	Unit
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V _{RMS}	35	70	140	280	420	560	700	V
Maximum D.C Blocking Voltage	V _{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current	I _{F(AV)}	3							A
Peak Forward Surge Current, 8.3ms single half sine-wave	I _{FSM}	100							A
Maximum Instantaneous Forward Voltage at 3.0A	V _F	1.3							V
Maximum D.C Reverse Current @ T _J =25°C	I _R	5							μA
at Rated D.C Blocking Voltage @ T _J =125°C		100							
Maximum Reverse Recovery Time (Note1)	T _{rr}	150			250	500		nS	
Typical Junction Capacitance (Note2)	C _J	40							pF
Typical Thermal Resistance (Note3)	R _{θJA}	45							°C/W
	R _{θJC}	15							
Operating Junction Temperature Range	T _J	-55 to +150							°C
Storage Temperature Range	T _{STG}	-55 to +150							°C

Note 1: Reverse Recovery Test Conditions: I_F=0.5A, I_R=1.0A, I_{RR}=0.25A

Note 2: Measured at 1MHz and applied reverse voltage of 4.0V D.C.

Note 3: P.C.B. mounted with 2.0" X 2.0" (5 X 5 cm) copper pad areas.

Ratings and Characteristic Curves

Fig.1 Maximum Average Forward Current Rating




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Instantaneous Forward Characteristics




Fig.4 Typical Junction Capacitance





Fig.5 Maximum Non-Repetitive Peak Forward Surge Current





FS3ABF THRU FS3MBF

Surface Mount Glass Passivated Fast Recovery Rectifiers

Ordering Information

Part No.	Package	Packing Code	Packing
FS3ABF THRU FS3MBF	SMBF	R50	5000pcs/Reel

Disclaimer

Specifications of the products displayed herein are subject to change without notice. JGD or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in JGD's terms and conditions of sale for such products, JGD assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of JGD products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify JGD for any damages resulting from such improper use or sale.